


0989.3 393
12.15.03



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 0 899 568 A2

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
03.03.1999 Bulletin 1999/09

(51) Int. Cl.⁶: G01N 30/88

(21) Application number: 98114476.9

(22) Date of filing: 31.07.1998

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: Okada, Kohji
Nishigyo-ku, Kyoto 610-1112 (JP)

(74) Representative:
WILHELMS, KILIAN & PARTNER
Patentanwälte
Eduard-Schmid-Strasse 2
81541 München (DE)

(30) Priority: 29.08.1997 JP 249741/97

(71) Applicant: SHIMADZU CORPORATION
Kyoto 604 (JP)

(54) System controller for analyzer

(57) The parameter display part (2) comprises a single upper-hierarchical parameter screen displaying only a selected parameter and a number of lower-hierarchical parameter screens corresponding to respective units displaying all parameters for the respective units, and switchably displaying. When selecting a parameter to be displayed on the upper-hierarchical parameter screen, moving the cursor to the parameter on any of the lower-hierarchical parameter screens and pressing the function key to select a display, the selected parameter is displayed on the upper-hierarchical parameter screen. When the parameter is selected again, the function key is pressed, and the display on the upper-hierarchical parameter screen is canceled

Fig. 3A

(a)

ANALYSIS FILE		FILE 0	
PUMP (B. GE)		DET. A	
T. FLOW	1.000 mL/min	WAVE	254 nm
B. CONC	50.0 %	AUXRNG	2
P. MAX	20.0 MPa	RESP	2
DET. B			
MONITOR			
A. PRES	9.8 MPa		
B. PRES	9.8 MPa		
C. PRES	9.8 MPa		
OVEN			
OVEN. T		40°C	
READY 15:00:00			

Fig. 3B

(b)

ANALYSIS FILE		FILE 0	
*** PUMP (LP. SE) ***			
T. FLOW	0.0 mL/min	P. MIN	0 MPa
B. CONC	60.0 %	LPGE. M	0
C. CONC	0.0 %	B. CURV	0
D. CONC	0.0 %	C. CURV	0
B. FLOW	3.000 mL/min	D. CURV	0
C. FLOW	4.000 mL/min	PASV	0
P. MAX	9.8 MPa	PBSV	0
		PCSV	0
* SEL/DEL		READY 15:00:00	

CURSOR

EP 0 899 568 A2

Description

BACKGROUND OF THE INVENTION

Field of the Invention

[0001] The present invention relates to the system controller of any of the following analyzers: a high-speed liquid chromatograph, a gas chromatograph, a liquid chromatograph/mass spectrometer or a gas chromatograph/mass spectrometer.

Description of the Prior Art

[0002] A high-speed liquid chromatograph comprises some of the following units: a feed pump, a detector, an automatic sampler and a column oven, all of which require parameter settings. Other analyzers also comprise some units requiring parameter settings. Such analyzers prepare a number of parameters to control these units, in order to cope with various analysis conditions. The analyzers comprise a system controller, which controls these units through these parameters. The system controller displays these parameters on a display.

[0003] A conventional system controller immovably displays these parameters on the same position of the display, and displays all available parameters on a single screen.

[0004] While there are many available parameters, those changed in daily analysis are extremely limited. When changing portion of the parameters, many unnecessary parameters displayed on the display are so obstructive that it takes time to search for the target parameter. If the parameter to be changed is displayed on a lower portion of the screen, it inconveniently takes time to move the cursor on the screen to select the parameter.

SUMMARY OF THE INVENTION

[0005] Accordingly, the object of the present invention is to make system controller parameter screens easier to view and easier to operate for the user, thereby eliminating any inconveniences.

[0006] The system controller for an analyzer, according to the present invention, comprises a parameter display part for displaying parameter conditions to control each unit, a parameter condition storage part, a parameter-input part, a parameter condition transmission part and a parameter input processing part. The parameter display part has an upper-hierarchical parameter screen displaying only the selected parameter(s) and a lower-hierarchical parameter screen displaying all parameters. The parameter condition storage part stores display/non-display modes on the upper-hierarchical parameter screen and parameter conditions of each parameter as data. The parameter-input part

inputs the display/non-display modes on the upper-hierarchical parameter screen and the parameter conditions of each parameter. The parameter condition transmission part transmits the parameter conditions for each parameter to a corresponding unit. The parameter input processing part transmits data from the parameter input part to the parameter condition storage part, and transmits the data stored in the parameter storage part to the parameter display part and the parameter condition transmission part.

[0007] The lower-hierarchical parameter screen displays every parameter of all available unit, and the upper-hierarchical parameter screen displays only the parameter(s) selected in the lower-hierarchical parameter screen. This parameter display part may have a single upper-hierarchical parameter screen and a number of lower-hierarchical parameter screens corresponding to respective units.

[0008] The parameter display part first displays the upper-hierarchical parameter screen. The displayed parameter screen can be switched by key operation. After selecting an arbitrary parameter on any of the lower-hierarchical parameter screens, the selected parameter is displayed on the upper-hierarchical parameter screen. The user can adjust the upper-hierarchical parameter screen displaying only the parameter(s) to be used in response to any desired analysis by selecting one or a plurality of parameters in any of the lower-hierarchical parameter screens, which then enables the user to bring the parameter screen of the system controller to a usable state.

[0009] The upper-hierarchical parameter screen of the system controller according to the present invention displays only the frequently changing parameter(s), whereby the parameter screen can be rendered easier to view and easier to operate for the user, thus eliminating any inconveniences.

[0010] The foregoing along with other objects, features, aspects and advantages of the present invention will become more apparent from the following detailed description of the present invention when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011]

Fig 1 is a block diagram showing the present invention.

Fig 2 is a block diagram showing an embodiment of the present invention.

Figs. 3(A) and 3(B) show exemplary upper- and lower-hierarchical parameter screens of the embodiment.

Fig 4 is a flow chart showing an operation procedure in the selection or cancellation of a parameter displayed on the upper-hierarchical screen of the embodiment.

Fig 5 is a flow chart showing a parameter set procedure of the embodiment.

DESCRIPTION OF THE PREFERRED EMBODIMENT

[0012] Fig 1 schematically shows a system controller for an analyzer according to the present invention. The parameter display part 2 is adapted to display parameter conditions for controlling each unit. The parameter display part 2 comprises a single upper-hierarchical parameter screen displaying only the selected parameter(s) and a number of lower-hierarchical parameter screens, which correspond to respective units and display all parameters for these respective units. These parameter screens are switched by key operation, to be displayed.

[0013] The parameter-input part 4 is adapted to input data of information as to whether or not each parameter is displayed on the upper-hierarchical parameter screen and the parameter conditions thereof.

[0014] The parameter condition storage part 10 is adapted to store the data inputted through the parameter-input part 4.

[0015] The parameter condition transmission part 8 transmits the parameter conditions for each parameter to a corresponding unit 12.

[0016] The parameter input processing part 6 transmits the data from the parameter input part 4 to the parameter condition storage part 10, and further transmits the data stored in the parameter storage part 10 to the parameter display part 2 and the parameter condition transmission part 8.

[0017] Fig 2 schematically shows an embodiment of the present invention, which is applied to a high-speed liquid chromatograph. The LCD (liquid crystal display unit) 14 is provided for the displaying of parameter conditions to control respective units. The LCD 14 switchably displays an upper-hierarchical parameter screen displaying only a selected parameter and lower-hierarchical parameter screens displaying all parameters for respective units. The keyboard 16 is provided to input parameter conditions and display/non-display modes on the upper-hierarchical parameter screen. The CPU 18 and the ROM 20 process the data inputted from the keyboard 16. The RAM 22 stores the data inputted from the keyboard 16 and processed in the CPU 18 and the ROM 20. The data processed in the CPU 18 and the ROM 20 are transmitted to units such as a pump and a detector through an interface 24, so that the respective units change conditions on the basis of signals thereof. The signals detected by the detector are processed in the CPU 18 and the ROM 20, to be thereafter transmitted to an external PC (personal computer).

[0018] Describing the relation between Figs. 1 and 2, the LCD 14 shown in Fig. 2 implements the parameter display part 2 shown in Fig. 1, the CPU 18 and the ROM 20 implement the parameter input processing part 6, the RAM 22 implements the parameter condition stor-

age part 10, and the interface 24 implements the parameter condition transmission part 8.

[0019] Fig. 3A shows an exemplary upper-hierarchical parameter screen (a) and Fig 3B shows an exemplary lower-hierarchical parameter screens (b). The lower-hierarchical parameter screen (b) displays all parameters of each unit. The screen (b) in Fig 3B, for example, displays all parameters of a pump unit. Such a screen (b) is prepared for every unit. On the other hand, the upper-hierarchical parameter screen (a) collects and displays only the parameter(s) selected in these lower-hierarchical screens (b).

[0020] Fig 4 is a flow chart showing an operation procedure in the selection or cancellation of parameters displayed on the upper-hierarchical parameter screen (a). The operation procedure for parameter selection or cancellation is now described with reference to Figs. 3A, 3B and 4. The following description is made with reference to pump parameters.

[0021] Parameter screen (a) refers to the upper-hierarchical parameter screen (Fig. 3(A)) displaying only frequently changing parameters selected by the user among the parameters of each unit. Parameter screen (b) refers to the lower-hierarchical parameter screen (Fig. 3(B)) which is present for each unit to display all parameters changeable in the unit.

[0022] When selecting a parameter screen from a menu screen, screen (a) is displayed. When screen (a) already displays only the parameters to be displayed, the parameter selection is finished.

[0023] If screen (a) displays no parameters to be displayed or parameters not to be displayed, the user presses the display screen switching key to display screen (b) of a unit (a pump in this case) including the parameters. The user finds out the parameters, to be displayed or erased on screen (a), on screen (b), and moves the cursor to the parameters on screen (b). At this time, the user presses the function key "SEL/DEL" on the lower left of screen (b) to select a display.

[0024] Selection marks "" are displayed on the left sides of the parameters, which are selected to be displayed on screen (a), on screen (b). When the user moves the cursor to the parameters and presses the function key "SEL/DEL" again, the selection is canceled, the display on screen (a) is also canceled and the display of the selection marks "" is erased. It is assumed here that "T. FLOW", "B. CONC" and "P. MAX" are selected.

[0025] After completing the selection of all necessary parameters on screen (b), the user presses the display screen-switching key to return the display to screen (a). Consequently, only "T. FLOW", "B. CONC" and "P. MAX" selected on screen (b) are displayed on the pump parameter display part of screen (a). Thus, the parameter selection is finished.

[0026] Fig. 5 is a flow chart showing a parameter set procedure. The parameter screens (a) and (b) are identical to those in Figs. 3A and 3B. The parameter set pro-

cedure is now described with reference to Fig. 5.

[0027] When the user selects a parameter screen from the menu screen, screen (a) is displayed (S1). If there is no changing of the parameter value, the parameter set procedure is finished (S2).

[0028] However, if there is changing of the parameter value, the user confirms whether or not the parameter to be changed is present on screen (a) (S3). The user changes the parameter value if the parameter is present (S4), and the parameter set procedure is finished if there are no other parameter values to be changed (S2).

[0029] If there are no parameters to be changed on screen (a), the user presses the display screen switching key to display screen (b) including the parameter to be changed (S5), and confirms whether or not the parameter to be changed is present on screen (b) (S6). The user changes the parameter value if the parameter is present (S7), and he presses the display screen-switching key to return to screen (a) (S6 → S1) if no parameter is present. If no other parameters are to be changed, the parameter set procedure is finished (S2).

[0030] In the case of changing the parameter this can be done by repeating the procedure of S2 → S3 → S4 if the parameter to be changed is present on screen (a); however, if the parameter to be changed is not present on screen (a), this must be done by repeating the procedure of S1 → S2 → S3 → S5 → S6 → S7 → S6 → S1 which is more complicated. Therefore, the parameter to be changed in daily analysis is preferably displayed on screen (a) in advance.

[0031] Although the present invention has been described and illustrated in detail, it is clearly understood that the same is by way of illustration and example only, and is not to be taken by way of limitation as the spirit and scope of the present invention is limited only by the terms of the appended claims.

Claims

1. The system controller for an analyzer comprising a parameter display part (2) displaying parameter conditions for the controlling of each unit characterized in that

said parameter display part (2) has an upper-hierarchical parameter screen displaying only the selected parameter(s) and at least one lower-hierarchical parameter screen displaying all parameters; and
said system controller further comprises;

a parameter condition storage part (10) storing display/non-display modes for each said parameter on said upper-hierarchical parameter screen and parameter conditions thereof as data;

a parameter input part (4) inputting said

display/non-display modes for each said parameter and said parameter conditions; a parameter condition transmission part (8) transmitting said parameter conditions for each said parameter to corresponding said unit; and

a parameter input processing part (6) transmitting data from the said parameter input part (4) to the said parameter condition storage part (10), and transmitting said data stored in the said parameter storage part (10) to the said parameter display part (2) and the said parameter condition transmission part (8).

2. The system controller for an analyzer in accordance with claim 1, wherein

the said upper-hierarchical parameter screen displays only a parameter selected on the said lower-hierarchical parameter screen.

3. The system controller for an analyzer in accordance with claim 1, wherein

the said parameter display part (2) comprises one said upper-hierarchical parameter screen and a number of said lower-hierarchical parameter screens corresponding to the respective said units, for displaying any said parameter screens.

4. The system controller for an analyzer in accordance with claim 3, being capable of switching the display of the any said parameter screen by key operation.

5. The system controller in accordance with claim 3, wherein

the said parameter display part (2) first displays the said upper-hierarchical parameter screen.

6. The system controller in accordance with claim 2, being adapted to select and cancel the said parameter displayed on the said upper-hierarchical parameter screen by selecting the said parameter on the said lower-hierarchical parameter screen with the cursor and pressing the prescribed key.

7. The system controller for an analyzer in accordance with claim 2, wherein

a selection mark is applied to the said parameter, which is selected and displayed on the said upper-hierarchical parameter screen, on the said lower-hierarchical parameter screen.

Fig.1




Fig.2





Fig. 3A

(a)

ANALYSIS FILE				FILE 0	
PUMP (B. GE)			DET. A		
T. FLOW	1.000	mL/min	WAVE	254	nm
B. CONC	50.0	%	AUXRNG	2	
P. MAX	20.0	MPa	RESP	2	
			DET. B		
MONITOR					
A. PRES	9.8	MPa			
B. PRES	9.8	MPa			
C. PRES	9.8	MPa			
			OVEN		
			OVEN.T 40 °C		
READY					
15:00:00					

Fig. 3B

(b)

ANALYSIS FILE				FILE 0	
*** PUMP (LP. SE) ***					
*T. FLOW	<input checked="" type="checkbox"/> 00	mL/min	P. MIN	0	MPa
*B. CONC	60.0	%	LPGE. M	0	
C. CONC	0.0	%	B. CURV	0	
D. CONC	0.0	%	C. CURV	0	
B. FLOW	3.000	mL/min	D. CURV	0	
C. FLOW	4.000	mL/min	PASV	0	
*P. MAX	9.8	MPa	PBSV	0	
			PCSV	0	
* SEL/DEL				READY	
		EXIT		15:00:00	


CURSOR 

Fig. 4







Fig. 5







Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 0 899 568 A3

(12) EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
22.08.2001 Bulletin 2001/34

(51) Int Cl.7: G01N 30/88

(43) Date of publication A2:
03.03.1999 Bulletin 1999/09

(21) Application number: 98114476.9

(22) Date of filing: 31.07.1998

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 29.08.1997 JP 24974197

(71) Applicant: SHIMADZU CORPORATION
Kyoto 604 (JP)

(72) Inventor: Okada, Kohji
Nishigyo-ku, Kyoto 610-1112 (JP)

(74) Representative: WILHELMS, KILIAN & PARTNER
Patentanwälte
Eduard-Schmid-Strasse 2
81541 München (DE)

(54) System controller for analyzer

(57) The parameter display part (2) comprises a single upper-hierarchical parameter screen displaying only a selected parameter and a number of lower-hierarchical parameter screens corresponding to respective units displaying all parameters for the respective units, and switchably displaying. When selecting a parameter to be displayed on the upper-hierarchical parameter

screen, moving the cursor to the parameter on any of the lower-hierarchical parameter screens and pressing the function key to select a display, the selected parameter is displayed on the upper-hierarchical parameter screen. When the parameter is selected again, the function key is pressed, and the display on the upper-hierarchical parameter screen is canceled

Fig. 3A


(a)

ANALYSIS FILE		FILE	0
PUMP (B. GE)		DET. A	
T. FLOW	1.000 mL/min	WAVE	254 nm
B. CONC	50.0 %	AUXRNG	2
P. MAX	20.0 MPa	RESP	2
		DET. B	
MONITOR			
A. PRES	9.8 MPa		
B. PRES	9.8 MPa		
C. PRES	9.8 MPa		
		OVEN	
		OVEN. T	40 °C
		READY	15:00:00

EP 0 899 568 A3

Fig. 3B

CURSOR



(b)

ANALYSIS FILE			FILE 0	
*** PUMP (LP. SE) ***				
* T. FLOW	<input checked="" type="checkbox"/> 0 0 mL/min	P. MIN	0	MPa
* B. CONC	6 0. 0 %	LPGE. M	0	
C. CONC	0. 0 %	B. CURV	0	
D. CONC	0. 0 %	C. CURV	0	
B. FLOW	3. 0 0 0 mL/min	D. CURV	0	
C. FLOW	4. 0 0 0 mL/min	PASV	0	
* P. MAX	9. 8 MPa	PBSV	0	
		PCSV	0	
* SEL DEL		 EXIT		READY 15:00:00



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 11 4476

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	PATENT ABSTRACTS OF JAPAN vol. 014, no. 298 (P-1068), 27 June 1990 (1990-06-27) & JP 02 093918 A (SHIMADZU CORP), 4 April 1990 (1990-04-04) * abstract *	1,4	601N30/88
Y	EP 0 709 756 A (HEWLETT PACKARD CO) 1 May 1996 (1996-05-01) * page 1 - page 4, line 26 *	1-6	
Y	GB 2 294 570 A (HEWLETT PACKARD CO) 1 May 1996 (1996-05-01) * page 2, line 8 - page 7, line 28 *	1-6	
X	GAY S: "MODULAR, DIGITAL, GAS ANALYZER ARCHITECTURE RE-THINKING THE APPROACH TO ANALYTICAL MEASUREMENTS" ADVANCES IN INSTRUMENTATION AND CONTROL, INSTRUMENT SOCIETY OF AMERICA, RESEARCH TRIANGLE PARK, US, vol. 49, no. PART 02, 1994, pages 197-208, XP000491427 ISSN: 1054-0032 * abstract; figures 2,4,6 *	1	
A	MATEK J E ET AL: "AN EXPERT SYSTEM CONTROLLER FOR GAS CHROMATOGRAPHY AUTOMATION" INSTRUMENTATION SCIENCE & TECHNOLOGY, US, J.E. WAMPLER, vol. 25, no. 2, 1 May 1997 (1997-05-01), pages 107-120, XP000749075 ISSN: 1073-9149 * abstract; figure 1 *	1	
-/--			
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 27 June 2001	Examiner Brison, O
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons A : technological background O : non-written disclosure P : intermediate document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

EPO FORM 1503 03/82 (PAC01)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 11 4476

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	US 4 873 623 A (LANE LESLIE A ET AL) 10 October 1989 (1989-10-10) * column 5, line 55 - column 6, line 9; figures 7,8 *	1	
A	WO 91 06050 A (APPLIED BIOSYSTEMS) 2 May 1991 (1991-05-02) * page 5, line 26 - page 6 *	1,6	
A	EP 0 596 205 A (HEWLETT PACKARD CO) 11 May 1994 (1994-05-11) * page 4, line 43-49 *	1,4	
A	US 5 611 059 A (BENTON ALLEN D ET AL) 11 March 1997 (1997-03-11) * abstract *	1	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 27 June 2001	Examiner Brison, O
CATEGORY OF CITED DOCUMENTS		I : theory or principle underlying the invention E : earlier patent document, not published on, or after the filing date D : document cited in the application L : document cited for other reasons A : technological background O : oral-written disclosure P : intermediate document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category			

EPF FORM 1502 03 B2 (P04/2011)

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 98 11 4476

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

27-06-2001

Patent document cited in search report:	Publication date	Patent family member(s)	Publication date
JP 02093918 A	04-04-1990	JP 2658271 B	30-09-1997
EP 0709756 A	01-05-1996	JP 8240581 A	17-09-1996
GB 2294570 A	01-05-1996	DE 19530842 A	02-05-1996
		JP 8286806 A	01-11-1996
US 4873623 A	10-10-1989	US 4679137 A	07-07-1987
		US 4805089 A	14-02-1989
		US 4951190 A	21-08-1990
		US 4967381 A	30-10-1990
		EP 0200441 A	05-11-1986
		JP 62103702 A	14-05-1987
		US 4843538 A	27-06-1989
		EP 0247743 A	02-12-1987
		JP 63032604 A	12-02-1988
WO 9106050 A	02-05-1991	AT 150879 T	15-04-1997
		DE 69030318 D	30-04-1997
		DE 69030318 T	16-10-1997
		EP 0496785 A	05-08-1992
		JP 6050460 B	29-06-1994
		JP 4507022 T	03-12-1992
		US 5841959 A	24-11-1998
EP 0596205 A	11-05-1994	JP 6222830 A	12-08-1994
US 5611059 A	11-03-1997	CA 2197876 A	14-03-1996
		EP 0777870 A	11-06-1997
		JP 10505179 T	19-05-1998
		WO 9607957 A	14-03-1996
		US 5706455 A	06-01-1998
		US 5675756 A	07-10-1997
		US 5929855 A	27-07-1999

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

